



Shipping: 2332 S 25th St
Omaha, NE 68105
Phone: (402) 344.4434
Fax: (402) 344.8091
www.BRAND-HYD.COM



83AFF NON ADJUSTABLE FLOW CONTROL INSTALLATION & USER GUIDE

SAFETY PRECAUTIONS

• It is the purchaser's responsibility to determine the suitability of any Brand Hydraulics Co. product for an intended application, and to ensure that it is installed in accordance with all federal, state, local, private safety and health regulations, codes and standards. Due to the unlimited variety of machines, vehicles and equipment on which our products can be used, it is impossible for Brand Hydraulics Co. to offer expert advice on the suitability of a product for a specific application. It is our customer's responsibility to undertake the appropriate precautions, testing and evaluation to prevent injury to the end-user.

SPECIFICATIONS:

- Rated for 0-10 gpm (0-37.9 lpm).
- Rated for 3000 psi (207 bar).
- Weighs 1/4 lb. (0.11 kg).
- 30-Micron Filtration Recommended.
- Port size #8 SAE (3/4-16).

FREQUENTLY ASKED QUESTIONS

Q: Can I change the flow of my valve?

A: The valves flow rate can be changed by drilling the orifice hole larger or replacing the spool with a different orifice diameter. The orifice diameter is determined from the customer's requested flow rate.

DIMENSIONAL DATA

